Supporting information

Low temperature catalytic oxidative coupling of methane in an electric field over Ce-W-O catalyst system

Kei Sugiura, Shuhei Ogo*, Kousei Iwasaki, Tomohiro Yabe, Yasushi Sekine

Department of Applied Chemistry, Waseda University, 3-4-1, Okubo, Shinjuku, Tokyo, 169-8555 Japan

*: Corresponding author: ogo@aoni.waseda.jp

Materials

A stock solution of 1.0 M of V(V) was prepared by dissolving 9.186 g of V_2O_5 and 6.194 g of NaOH in 100 mL of water (0.5 M $V_2O_5/1.5$ M NaOH). Other reagents were of analytical grade and were used as received.

Preparations of tetrabutylammonium (TBA) salt of Keggin-type HPAs

Preparation of $(TBA)_3[PW_{12}O_{40}]$ (denoted as $TBA-PW_{12}$)

An aqueous solutions of 1.0 M Na₂WO₄ (5 mL), conc. HCl (4.2 mL), and 1.0 M NaH₂PO₄ solution (0.5 mL) were poured into 100 mL vessel in the order, and diluted with 100 mL of water. The resultant solution was aged at 353 K for 2 days in static. After the resulting clear solution had been cooled to room temperature, three equivalents (0.484 g) of tetrabutylammonium (TBA) bromide, $[CH_3(CH_2)_3]_4NBr$, was added to solution. After solution stirred at room temperature for 30 min, the resultant white solid was filtered off, washed with distilled water (50 mL) and ethanol (20 mL), and dried at 393 K overnight. IR(KBr): v = 1079 (m), 975 (s), 895 (s), 814 (s) cm⁻¹.

Preparation of $(TBA)_4[PW_{11}V_1O_{40}]$ (denoted as $TBA-PW_{11}V_1$)

An aqueous solutions of 1.0 M Na₂WO₄ (5 mL), 0.5 M V₂O₅/1.5M NaOH (0.5 mL), conc. HCl (4.2 mL), and 1.0 M NaH₂PO₄ solution (0.5 mL) were poured into 100 mL vessel in the order, and diluted with 100 mL of water. The resultant solution was aged at 353 K for 2 days in static. After the resulting yellow solution had been cooled to room temperature, four equivalents (0.645 g) of tetrabutylammonium (TBA) bromide, [CH₃(CH₂)₃]₄NBr, was added to solution. After solution stirred at room temperature for

30 min, the resultant yellow solid was filtered off, washed with distilled water (50 mL) and ethanol (20 mL), and dried at 393 K overnight.

IR(KBr): v = 1095 (w), 1069 (w), 962 (s), 889 (m), 808 (vs) cm⁻¹.

Preparation of $(TBA)_5[PW_{10}V_2O_{40}]$ (denoted as $TBA-PW_{10}V_2$)

An aqueous solutions of 1.0 M Na₂WO₄ (5 mL), 0.5 M V₂O₅/1.5M NaOH (2.0 mL), conc. HCl (4.2 mL), and 1.0 M NaH₂PO₄ solution (0.5 mL) were poured into 100 mL vessel in the order, and diluted with 100 mL of water. The resultant solution was aged at 353 K for 2 days in static. After the resulting orange solution had been cooled to room temperature, five equivalents (0.806 g) of tetrabutylammonium (TBA) bromide, [CH₃(CH₂)₃]₄NBr, was added to solution. After solution stirred at room temperature for 30 min, the resultant orange solid was filtered off, washed with distilled water (50 mL) and ethanol (20 mL), and dried at 393 K overnight.

IR(KBr): v = 1095(w), 1063 (w), 960 (s), 889 (m), 808 (vs) cm⁻¹.

Table S1 Catalytic activities over 40 wt%TBA-PW₁₂O₄₀/CeO₂ in various temperatures without electric field^a

Condition	External temp.	CH ₄ Conv.	O ₂ Conv.	C ₂ Sel.	C ₂ Yield
Condition	/ K	/ %	/ %	/ %	/ %
	573	0.1	0.7	0.0	0.0
	673	0.1	2.1	0.0	0.0
without EF	773	0.4	4.2	0.0	0.0
WILLIOUL EF	873	1.3	3.8	0.0	0.0
	973	1.3	5.9	0.0	0.0
	1073	5.0	14.8	3.5	0.2

^a Feed gas $CH_4:O_2:Ar=25:15:60$ SCCM, catalyst weight: 100 mg, furnace temperature: 573-1073 K

Table S2 Effect of input current on catalytic activity over 40 wt%TBA-PW₁₂O₄₀/CeO₂ in the electric field^a

Current	T_{tc}^{b}	Voltage	CH ₄ Conv.	O ₂ Conv.	C ₂ Sel.	C ₂ Yield	Field intensity	Faradaic number
/ mA	/ K	/ kV	/ %	/ %	/ %	/ %	$/ V mm^{-1}$	/ -
3.0	689	1.3	14.9	20.6	43.4	6.4	260	83.3
5.0	772	0.8	32.5	40.1	40.0	13.0	160	109
7.0	863	0.7	52.8	63.3	32.0	16.9	140	127

^a Feed gas CH₄:O₂:Ar = 25:15:60 SCCM, input current: 3.0-7.0 mA, catalyst weight: 100 mg, furnace temperature: 423 K

Table S3 Catalytic activities over 40 wt%TBA-HPAs/CeO₂ in the electric field^a

Catalysts	T _{tc} ^b	Voltage	CH ₄ Conv.	O ₂ Conv.	C ₂ Sel.	C ₂ Yield	Field intensity	Faradaic number
Catalysis	/ K	/ kV	/ %	/ %	/ %	/ %	/ V mm ⁻¹	/ -
TBA-PW ₁₂ /CeO ₂	772	0.8	32.5	40.1	40.0	13.0	160	109
TBA-PW ₁₁ V ₁ /CeO ₂	754	0.8	26.4	34.7	31.8	8.4	136	83.4
TBA-PW ₁₀ V ₂ /CeO ₂	708	0.7	25.5	34.2	31.4	8.0	130	81.1
CeO_2	675	0.1	28.2	100	0.2	0.1	20	93.1

^a Feed gas CH₄:O₂:Ar = 25:15:60 SCCM, input current: 5.0 mA, catalyst weight: 100 mg, furnace temperature: 423 K

TBA-HPAs: TBA-PW_{12-x}V_xO₄₀ (x = $0\sim2$)

^b Catalyst bed temperature measured by a thermocouple

^b Catalyst bed temperature measured by a thermocouple

Table S4 Catalytic activities over various oxide catalysts in the electric field (power fixing)^a

Catalyata	T _{te} ^b	Current	Power	CH ₄ Conv.	O2 Conv.	C ₂ Sel.	C ₂ Yield	Field intensity	Faradaic number
Catalysts	/ K	/ mA	/ W	/ %	/ %	/ %	/ %	/ V mm ⁻¹	/ -
TBA-PW ₁₂ /CeO ₂	595	1.5	2.6	5.8	14.5	43.7	2.6	315	61.4
$Ce_2(WO_4)_3/CeO_2$	649	3.0	2.7	13.6	18.5	39.0	5.3	225	73.9
WO ₃ /CeO ₂	634	3.0	2.4	14.3	20.8	32.4	4.6	145	74.0
$Ce_2(WO_4)_3$	659	3.0	2.1	9.7	11.6	41.2	4.0	189	53.3
WO_3	586	20.0	2.0	0.2	1.7	0.0	0.0	29	0.1

 $^{^{}a}$ Feed gas CH₄:O₂:Ar = 25:15:60 SCCM, input current: 1.5, 3.0, 20.0 mA, catalyst weight: 100 mg, furnace temperature: 423 K

Table S5 Catalytic activities over various oxide catalysts in the electric field (catalyst bed temperature fixing)^a

Catalysts	T _{te} ^e	Voltage	CH ₄ Conv.	O2 Conv.	C ₂ Sel.	C ₂ Yield	Field intensity	Faradaic number
Catalysts	/ K	/ kV	/ %	/ %	/ %	/ %	$/ \mathrm{~V~mm}^{\text{-1}}$	/ -
TBA-PW ₁₂ /CeO ₂	689	1.3	14.9	20.6	43.4	6.4	260	83.3
$Ce_2(WO_4)_3/CeO_2$	649	0.9	13.6	18.5	39.0	5.3	225	73.9
WO_3/CeO_2	634	0.8	14.3	20.8	32.4	4.6	145	74.0
$Ce_2(WO_4)_3$	659	0.7	9.7	11.6	41.2	4.0	189	53.3
WO ₃ b	684	0.1	0.0	14.3	0.0	0.0	29	0.0

^a Feed gas $CH_4:O_2:Ar = 25:15:60$ SCCM, input current: 3.0 mA, catalyst weight: 100 mg, furnace temperature: 423 K (b 673 K)

Table S6 $\,$ Temperature dependency over $Ce_2(WO_4)_3/CeO_2$ in the electric field (power fixing)^a

Furnace temp.	T _{tc} ^b / K	Current / mA	Voltage / kV	Power / W	CH ₄ Conv.	O ₂ Conv.	C ₂ Sel.	C ₂ Yield	Field intensity
423	649	3.0	0.9	2.7	13.6	18.5	39.0	5.3	225
673	830	5.0	0.5	2.5	16.2	36.9	33.7	5.5	122
873	993	10.0	0.3	3.0	18.7	47.1	18.0	3.4	77

^a Feed gas $CH_4:O_2:Ar=25:15:60$ SCCM, input current: 3.0, 5.0, 10.0 mA, catalyst weight: 100 mg, furnace temperature: 423, 673, 873 K

^b Catalyst bed temperature measured by a thermocouple

^c Catalyst bed temperature measured by a thermocouple

^b Catalyst bed temperature measured by a thermocouple

Table S7 Result of periodic operation test (after 2 and 12 min from CH_4 supply) over $Ce_2(WO_4)_3/CeO_2$ without electric field at 1073 K^a

Cycle number	Time	CH ₄ Conv.	C ₂ Sel.	CO _x Sel.	C ₂ Yield
	/ min	/ %	/ %	/ %	/ %
1	2	0.17	11.6	88.4	0.02
1	12	0.39	4.1	95.9	0.02
2.	2	0.18	8.3	91.7	0.02
	12	0.37	4.5	95.5	0.02
3	2	0.20	8.6	91.4	0.02
	12	0.39	4.4	95.6	0.02
4	2	0.22	7.7	92.3	0.02
4	12	0.40	4.3	95.7	0.02
5	2	0.23	8.0	92.0	0.02
	12	0.44	4.1	95.9	0.02

 $^{^{\}rm a}$ Feed gas: O₂:Ar = 15:60 SCCM, CH₄:Ar = 25:60 SCCM, catalyst weight: 100 mg, furnace temperature: 1073 K

Table S8 Results of *in-situ* Raman over Ce₂(WO₄)₃/CeO₂ with and without electric field

	Conditions	Voltage		nber / cm ⁻¹ WO ₄) ₃
		/ kV	W ^I -O	W ^{II} -O
(a)	inert (RT)	-	948	929
(b)	without EF (air, 603-703 K)	-	945	927
(c)	with EF (air, 6.0 mA)	0.69	937	922
(d)	with EF (CH_4 , 6.0 mA)	0.73	938	922
(e)	with EF (CH_4+O_2 , 6.0 mA)	0.67	938	922
(f)	without EF after (e)	-	947	930

Table S9 Result of curve fitting over Ce₂(WO₄)₃/CeO₂ catalysts in various state^a

Conditions	bond	CN	R/A	dE / eV	DW/A^2	R-factor
	W-O		1.730			
	W-O		1.768			
as-made	W-O	1.05	1.812	3.652	0.0040	0.047
	W-O		1.818			
	W-O		2.197			
	W-O		1.706			
often ()	W-O		1.743			
after O ₂ supply	W-O	1.01	1.787	-1.233	0.0038	0.050
in periodic operation test	W-O		1.792			
	W-O		2.166			
	W-O		1.753			
aftan 1 amala	W-O		1.790			
after 1 cycle	W-O	0.84	1.836	8.669	0.0035	0.047
in periodic operation test	W-O		1.841			
	W-O		2.225			
	W-O		1.709			
often magation	W-O		1.746		0.0040	
after reaction	W-O	0.88	1.790	-2.286		0.014
with electric field	W-O		1.795			
	W-O		2.170			

^a k- range: 3-11Å, R-range: 1-2.3 Å

Table S10 BET surface area of various catalysts as made and after reaction with electric field

Catalysts		surface area m ² g ⁻¹
	as made	after reaction
TBA-PW ₁₂ /CeO ₂	52.1	5.6
$Ce_2(WO_4)_3/CeO_2$	3.6	3.2
WO ₃ /CeO ₂	90.1	18.6
$Ce_2(WO_4)_3$	1.0	0.7




Fig. S1 Raman spectra of TBA-PW $_{12}O_{40}$ and 40 wt%TBA-PW $_{12}O_{40}$ /CeO $_2$ before and after reaction with electric field.

 \bigcirc : CeO₂, \diamondsuit : [PW₁₂O₄₀]³⁻, \triangle : WO₃, \blacksquare : Ce₂(WO₄)₃, \times : Unidentified




Fig. S2 XRD patterns of 40 wt%TBA-PW₁₂O₄₀/CeO₂ before and after reaction with electric field.

 \bigcirc : CeO₂, \triangle : WO₃, \blacksquare : Ce₂(WO₄)₃, \blacktriangledown : Ce₂WO₆




Fig. S3 IR spectra of TBA-PW₁₂O₄₀ and 40 wt%TBA-PW₁₂O₄₀/CeO₂ before and after reaction with electric field.





Fig. S4 Catalytic activity in the conventional reaction (573-1073 K) over 40 wt% TBA-PW₁₂O₄₀/CeO₂ after the reaction with electric field (423 K, 3.0 mA, 10 min). ○: CH₄ Conv., □: O₂ Conv., ◆: C₂ Sel.






Fig. S5 XRD patterns of various oxide catalysts.

(a) as-made, (b) after reaction with electric field

○: CeO₂, ■: Ce₂(WO₄)₃





Fig. S6 Time course of the CH₄ and O₂ conversion and C₂ selectivity for OCM over Ce₂(WO₄)₃/CeO₂ in the electric field (423 K, 3.0 mA).

 \bigcirc : CH₄ Conv., \square : O₂ Conv., \spadesuit : C₂ Sel.



10180 10190 10200 10210 10220 10230 10240 10250 Energy / eV

Fig. S7 XANES spectra at W L_3 -edge over WO₃, $Ce_2(WO_4)_3$ and $Ce_2(WO_4)_3/CeO_2$ catalysts in various state.

(a) WO₃, (b) Ce₂(WO₄)₃, (c) Ce₂(WO₄)₃/CeO₂ as-made, (d) Ce₂(WO₄)₃/CeO₂ after O₂ supply in periodic operation test, (e) Ce₂(WO₄)₃/CeO₂ after 1 cycle in periodic operation test, (f) Ce₂(WO₄)₃/CeO₂ after reaction with electric field




Fig. S8 EXAFS spectra at W L_3 -edge over WO_3 , $Ce_2(WO_4)_3$ and $Ce_2(WO_4)_3/CeO_2$ catalysts in various state.

(a) WO₃, (b) Ce₂(WO₄)₃, (c) Ce₂(WO₄)₃/CeO₂ as-made, (d) Ce₂(WO₄)₃/CeO₂ after O₂ supply in periodic operation test, (e) Ce₂(WO₄)₃/CeO₂ after 1 cycle in periodic operation test, (f) Ce₂(WO₄)₃/CeO₂ after reaction with electric field




Fig. S9 Possible reaction mechanism of OCM over $Ce_2(WO_4)_3/CeO_2$ catalyst in the electric field:

(a) OCM occurred using lattice oxygen of $Ce_2(WO_4)_3$ (short W-O bond in distorted WO₄ unit); (b) Reproduction of lattice oxygen by gas-phase oxygen.




Fig. S10 Schematic diagram of reactor.




Fig. S11 Schematic diagram of reactor for *in-situ* Raman.